

LTB9 | 4 x 1000W Metal Halide Lamps

TOTAL 360,000 LUMENS | MAST HEIGHT: 9,000 mm



RETRACTED POSITION

Operated in conjunction with auxiliary power source

REFERENCE STANDARDS

JCB Lighting Towers are CE certified and conform to the following Directives (subject to a country requiring such standard):

- 2006/95/EC Low voltage
- 2004/108/CE Electromagnetic compatibility
- Ambient reference conditions 1000mbar, 25°C, 30% relative humidity ISO3046

Information based on standard specification equipment unless otherwise stated.

ELECTRICAL PERFORMANCE

Input		32A CEE form 3 Phase Plug
Power Consumption	kW	4
Circuit Breaker		3 Pole inc. Earth
Lamp Type		Metal Halide
Lamp Power	W	1,000
Number of Lamps		4
Lamp Power	Lumens	360,000
Lamp IP Rating		IP65
Auxiliary Output Sockets		2 x 16A Single Phase CEE

WEIGHT AND DIMENSIONS

Length (Deployed/Transport)	mm	1950 / 1600
Width (Deployed/Transport)	mm	2250 / 1300
Height (Deployed/Transport)	mm	9000 / 2230
Weight	kg	755
Mast Raise to Full Height	s	13
Mast Lower to Travel	s	25
Maximum Operational Wind Speed	Km/h	80

Operated in conjunction with auxiliary power source

FEATURES

4 x Individual Lamp Breakers	•
2 x CEE 16A Single Phase Output Sockets	•
1 x CEE 32A 3 Phase Input Plug	•
Preparation for Earth Spike	•
Remote Light Control	Δ
360° Manual Rotation with Lock	•
Remote Operated Light Angle Adjuster	Δ
Timer Control of Lights	Δ
Solar Cell Control of Lights	Δ
Standard: • Not Available: x Optional: Δ	